

Technical Data		Audi A5 Coupé 35 TFSI (110 kW)	
Program for Germany		Status: 07/29/2020	
Engine / electrics			
Engine type	Inline 4-cylinder engine		
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder		
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 12.2		
Max. power output in kW (PS) / rpm	110 (150) / 4000 - 6000		
Max. torque in Nm (<i>lb-ft</i>) / at rpm	270 (199.1) / 1300 - 3850		
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler		
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter		
Emissions standard	EU6		
Start-stop / REM	yes / yes		
Battery in A / Ah	380 / 68		
Max. electrical output at 12V in kilowatts	3.1		
On-board voltage 1 in volts	12		
Drivetrain / transmission			
Drive type	Front-wheel drive		
Clutch	Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel		
Transmission type	6-speed manual gearbox		
Transmission ratio in 1st/2nd gear	3.778 / 2.045		
Transmission ratio in 3rd/4th gear	1.276 / 0.941		
Transmission ratio in 5th/6th gear	0.784 / 0.667		
Reverse gear ratio / final drive ratio 1-2 / 2-3	3.333 / 2.5 / 1.364		
Suspension / steering / brakes			
Type and design of front-axle suspension	5-link front axle; tubular anti-roll bar		
Type and design of rear-axle suspension	5-link rear axle; tubular anti-roll bar		
Steering	Electromechanical steering with speed-dependent power assistance		
Steering ratio	15.9		
Turning circle in m (<i>ft</i>)	11.5 (37.7)		
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist		
Tires (basic)	225/50 R 17		
Wheels (basic)	Alloy 7.5 J x 17"		
Performance / acoustics			
Top speed in km/h (<i>mph</i>)	210 (130.5)		
Limited	yes		
Acceleration, 0-100 km/h (0-62.1 <i>mph</i>)	8.7		
Fuel type / octane value	Gasoline / 95		
Fuel standard	DIN EN 228 not available		
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	70.3 / 68		

Consumption / emissions*	
Fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (<i>US mpg</i>)	8.0 - 7.6 (29.4 - 30.9) / 5.0 - 4.6 (47.0 - 51.1) / 6.1 - 5.7 (38.6 - 41.3)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	139 - 130 (223.7 - 209.2)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 25 / 25
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1440 (3174.7) / 1515 (3340.0) / 1935 (4265.9)
Front/rear axle load limit in kg (<i>lb</i>)	1010 (2226.7) / 1025 (2259.7)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1600 (3527.4) / 1400 (3086.5) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 (165.3) / 80 (176.4)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	7.6 (2.0)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	5.2 (5.5)
Fuel tank capacity in liters (<i>US gal</i>)	54 (14.3)
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 2
Number of seats	4
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.26 / 2.14 (23.0)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4697 (15.4) / 1846 (6.1) / 1371 (4.5) / -
Width including mirrors in mm (<i>ft</i>)	2029 (6.7)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2764 (9.1) / 1587 (5.2) / 1568 (5.1)
Overhang angle of steel springs, front / rear in degrees	12.50 / 12.90
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	669 (2.2) / -
Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>)	- / 450 (15.9)

*Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used