

Technical Data	Audi e-tron S
Program for Germany	Status: 09/10/2020
<b>Engine / electrics</b>	
Peak electrical output in kW	320
Continuous electrical output in kW	140
Peak electrical output boost in kW	370
Electrical torque output in Nm ( <i>lb-ft</i> )	808 (596.0)
Electrical torque output boost in Nm ( <i>lb-ft</i> )	973 (717.6)
Battery type	Lithium-ion
Battery energy content in kWh	95
Battery in A / Ah	380 / 68
Max. electrical output at 12V in kilowatts	3
On-board voltage 1 in volts	12
On-board voltage 3 in volts	400
Start-stop / REM	no / yes
Emissions standard	-
<b>Drivetrain / transmission</b>	
Drive type	quattro permanent all-wheel drive
Transmission type	single-speed
Transmission ratio in 1st/2nd gear	9.205 / not available
Reverse gear ratio / final drive ratio 1-2	Not available / 9.205
<b>Suspension / steering / brakes</b>	
Type and design of front-axle suspension	Five-link front axle; tubular anti-roll bar; air spring suspension
Type and design of rear-axle suspension	Five-link rear axle; tubular anti-roll bar; air spring suspension
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.9
Turning circle ( <i>ft</i> )	12.2 (40.0)
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Basic tires, front axle	285/45 R 20 112 H XL (extra load) -
Basic tires, rear axle	285/45 R 20 112 H XL (extra load) -
Wheels, front axle	Cast aluminum flow forming 10,0Jx20"
Wheels, rear axle	Cast aluminum flow forming 10,0Jx20"
<b>Performance / acoustics</b>	
Top speed in km/h ( <i>mph</i> )	210 (130.5)
Limited	yes
Electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in seconds	5.1
Electrical acceleration boost, 0-100 km/h (62.1 <i>mph</i> ) in seconds	4.5
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	- / - / 68
<b>Consumption / range</b>	
Electric power consumption, combined, in kWh/100 km (62.1 <i>mi</i> )*	28,4–26,8 (WLTP); 28,2 (NEDC)
CO <sub>2</sub> emissions, combined, in g/km ( <i>g/mi</i> )	0
Electrical range based on current consumption in combined WLTP driving cycle in km ( <i>mi</i> )*	up to 364 (226.2)

<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2620 (5776.1) / 2695 (5941.5) / 3245 (7154.0)
Front/rear axle load limit in kg ( <i>lb</i> )	1565 (3450.2) / 1750 (3858.1)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1800 (3968.3) / 1800 (3968.3) // 750 (1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 80 (176.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	21.6 (5.7)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.28 / 2.71 (29.2)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4902 (16.1) / 1976 (6.5) / not available / 1629 (5.3)
Width including mirrors in mm ( <i>ft</i> )	2189 (7.2)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2928 (9.6) / 1683 (5.5) / 1683 (5.5)
Overhang angle of air spring front/rear in degrees	15.4 / 20.0
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	Not available / 800 (2.6)
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	660 (23.3) / not available
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1725 (60.9)
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	660 (23.3)

\* Figures depend on the equipment selected