

Audi e-tron S Sportback



370 kW

Drivetrain / transmission / battery

Drive type	All-wheel drive
Number of electric motors front axle / rear axle	1 / 2
Transmission type	2-stage ratio planetary gearbox with a single gear
Peak electrical output in kW	320
Peak electrical output boost in kW	370
Continuous electrical output in kW	140
Electrical torque output boost in Nm (<i>lb-ft</i>)	973 (717.6)
Battery type / number of cells	Lithium-Ion / 432
Gross / net battery capacity in kWh	95 / 86
Max. charging capacity AC / DC in kW	11 / 150
Max. charging capacity AC / DC optional in kW	22 / -
Charging time DC 5-80% in min	30 with HPC 150 kW
Charging time AC 0-100%, 3ph 16A@230V in min	555
Charging time AC 0-100%, 3ph 16A@230V optional in min	285
On-board voltage 1 in volts	12

Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Tires (basic)	285/45 R 20
Wheels (basic)	Cast aluminum flow forming 10 J x 20"
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.9
Turning circle in m (<i>ft</i>)	12.2 (40.0)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: aluminum fixed caliper; rear: floating caliper with integrated electronic parking brake
Brake disk diameter front / rear in mm (<i>in</i>)	- / 350 (13.8)

Performance / range / acoustics

Top speed in km/h (<i>mph</i>)	210 (130.5) (limited)
electrical acceleration, 0-100 km/h (62.1 <i>mph</i>) in s	5.1
Electrical acceleration boost, 0-100 km/h (62.1 <i>mph</i>) in s	4.5
Electrical range, combined according to WLTP in km (<i>mi</i>)	379 - 347 (235.5 - 215.6)

Consumption / emission*

Efficiency class	A+++
Electric power consumption, combined according to NEDC in kWh/100 km (62.1 <i>mi</i>)	26.0 - 24.6
Electric power consumption, combined according to WLTP in kWh/100 km (62.1 <i>mi</i>)	28.1 - 25.7
CO2 emissions, combined in g/km (<i>g/mi</i>)	0

Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	20 / 27 / 25

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (lb)	2655 / 2730 / 3280 (5853.3 / 6018.6 / 7231.2)
Front / rear axle load limit in kg (lb)	1585 / 1805 (3494.3 / 3979.3)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	1800 / 1800 // 750 (3968.3 / 3968.3 // 1653.5)
Roof load limit / permissible nose weight in kg (lb)	75 / 80 (165.3 / 176.4)

Dimensions / body

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5/ 5
Drag coefficient C _d / frontal area A in m ² (sq ft)	0.26 / 2.71 (29.2)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (ft)	4902 / 1976 / - / 1615 (16.1 / 6.5 / - / 5.3)
Vehicle width, including mirrors, in mm (in)	2189 (7.2)
Wheelbase // track width front / rear in mm (ft)	2928 // 1683 / 1683 (9.6 // 5.5 / 5.5)
Height of loading edge in mm (ft)	800 (2.6)
Open luggage compartment - behind the 2nd seat row in l (cu ft)	555 (19.6)
Largest luggage capacity - behind the 1st seat row in l (cu ft)	1594 (56.3)

* Figures depend on the equipment selected.