

<b>Technical Data</b>		<b>Audi Q2 35 TDI quattro S tronic (110 kW)</b>	
<b>Program for Germany</b>		Status: 10/05/2020	
<b>Engine / electrics</b>			
Engine type	Inline 4-cylinder engine		
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder		
Displacement in cc / bore x stroke in mm / compression	1968 / 81.0 x 95.5 / 16.0		
Max. power output in kW (PS) / rpm	110 (150) / 3000 - 4200		
Max. torque in Nm ( <i>lb-ft</i> ) / at rpm	360 (265.5) / 1600 - 2750		
Mixture preparation	Common rail fuel injection system, intercooler		
Exhaust emission control	Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter		
Emissions standard	EU6		
Start-stop / REM	yes / yes		
Battery in A / Ah	420 / 70		
Max. electrical output at 12V in kilowatts	1.6		
On-board voltage 1 in volts	12		
<b>Drivetrain / transmission</b>			
Drive type	All-wheel drive		
Type of center differential	Electronically controlled multi-plate clutch		
Type of rear axle differential	Standard		
Clutch	2 electrohydraulically controlled multi-plate clutches in an oil bath, dual-mass flywheel		
Transmission type	7-speed S tronic		
Transmission ratio in 1st/2nd gear	3.579 / 2.750		
Transmission ratio in 3rd/4th gear	1.677 / 0.889		
Transmission ratio in 5th/6th gear	0.677 / 0.722		
Transmission ratio in 7th/8th gear	0.561 / -		
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.9 / 4.471 / 3.304		
<b>Suspension / steering / brakes</b>			
Type and design of front-axle suspension	McPherson struts, front		
Type and design of rear-axle suspension	4-link rear axle		
Steering	Electromechanical progressive steering with speed-dependent power assistance		
Steering ratio	14.1		
Turning circle in m ( <i>ft</i> )	11.1 (36.4)		
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist		
Tires (basic)	205/60 R 16 92 V		
Wheels (basic)	Alloy 6 J x 16"		
<b>Performance / acoustics</b>			
Top speed in km/h ( <i>mph</i> )	210 (130.5)		
Limited	no		
Acceleration, 0-100 km/h ( <i>0-62.1 mph</i> )	8.2		
Fuel type / octane value	Diesel / -		
Fuel standard	DIN EN 590 (Diesel)		
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	76.7 / 68		

<b>Consumption / emissions*</b>	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers ( <i>US mpg</i> )	5.6 - 5.4 (42.0 - 43.6) / 4.4 - 4.1 (53.5 - 57.4) / 4.8 - 4.6 (49.0 - 51.1)
CO <sub>2</sub> emissions combined in grams per kilometer ( <i>g/mi</i> )	128 - 122 (206.0 - 196.3)
<b>Servicing / guarantee (Germany)</b>	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 20 / 23
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1495 (3295.9) / 1570 (3461.3) / 2060 (4541.5)
Front/rear axle load limit in kg ( <i>lb</i> )	1105 (2436.1) / 1030 (2270.8)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1800 (3968.3) / 1800 (3968.3) // 750 (1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	60 (132.3) / 75 (165.3)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	13.2 (3.5)
Engine oil capacity, including filter (change volume) in liters ( <i>US qt</i> )	5.5 (5.8)
Fuel tank capacity in liters ( <i>US gal</i> )	55 (14.5)
AdBlue fuel tank capacity in liters ( <i>US gal</i> )	12 (3.2)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.32 / 2.29 (24.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4208 (13.8) / 1794 (5.9) / 1537 (5.0) / -
Width including mirrors in mm ( <i>ft</i> )	2009 (6.6)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2601 (8.5) / 1546 (5.07) / 1542 (5.06)
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	740 (2.4) / -
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	355 (12.5) / -
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1000 (35.3)

\*Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tires/wheels used