

<b>Technical Data</b>		<b>Audi A3 Sportback 30 TFSI S tronic (81 kW)</b>
<b>Program for Germany</b>	Status: 10/02/2020	
<b>Engine / electrics</b>		
Engine type	Inline 3-cylinder engine	
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	999 / 74.5 x 76.4 / 11.5	
Max. power output in kW (PS) / rpm	81 (110) / 5500	
Max. torque in Nm ( <i>lb-ft</i> ) / at rpm	200 (147.5) / 2000 - 3000	
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler	
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter	
Emissions standard	EU6	
Start-stop / REM	yes / yes	
Battery in A / Ah	320 / 59	
Max. electrical output at 12V in kilowatts	3	
On-board voltage 1 in volts	12	
On-board voltage 2 in volts	48	
<b>Drivetrain / transmission</b>		
Drive type	Front-wheel drive	
Clutch	2 hydraulically actuated dry clutches, asbestos/lead-free linings, dual-mass flywheel	
Transmission type	7-speed S tronic	
Transmission ratio in 1st/2nd gear	3.765 / 2.273	
Transmission ratio in 3rd/4th gear	1.531 / 1.133	
Transmission ratio in 5th/6th gear	1.176 / 0.956	
Transmission ratio in 7th/8th gear	0.795 / -	
Reverse gear ratio / final drive ratio 1-2 / 2-3	4.17 / 4.438 / 3.227	
<b>Suspension / steering / brakes</b>		
Type and design of front-axle suspension	McPherson struts, front	
Type and design of rear-axle suspension	Torsion-beam rear axle	
Steering	Electromechanical steering with speed-dependent power assistance	
Steering ratio	14.9	
Turning circle ( <i>ft</i> )	11.1 (36.4)	
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic)	205/55 R 16 91 V	
Wheels (basic)	Alloy 7 J x 16"	
<b>Performance / acoustics</b>		
Top speed in km/h ( <i>mph</i> )	204 (126.8)	
Limited	no	
Acceleration, 0-100 km/h (0-62.1 <i>mph</i> )	10.6	
Fuel type / octane value	Gasoline / 95	
Fuel standard	DIN EN 228 (gasoline)	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	68.4 / 68	

<b>Consumption / emissions*</b>	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers ( <i>US mpg</i> )	5.2 - 5.1 (45.2 - 46.1) / 4.1 - 3.9 (57.4 - 60.3) / 4.5 - 4.3 (52.3 - 54.7)
CO <sub>2</sub> emissions combined in grams per kilometer ( <i>g/mi</i> )	104 - 99 (167.4 - 159.3)
<b>Servicing / guarantee (Germany)</b>	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	14 / 20 / 21
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1280 (2821.9) / 1355 (2987.3) / 1835 (4045.5)
Front/rear axle load limit in kg ( <i>lb</i> )	985 (2171.6) / 935 (2061.3)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1500 (3306.9) / 1300 (2866.0) // 670 (1477.1)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 80 (176.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	8.9 (2.4)
Engine oil capacity, including filter (change volume) in liters ( <i>US qt</i> )	4 (4.2)
Fuel tank capacity in liters ( <i>US gal</i> )	45 (11.9)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.29 / 2.17 (23.4)
Standard dimensions (length / width excluding mirrors / height with steel springs) in mm ( <i>ft</i> )	4343 (14.2) / 1816 (6.0) / 1449 (4.8)
Width including mirrors in mm ( <i>ft</i> )	1984 (6.5)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2636 (8.6) / 1554 (5.1) / 1525 (5.0)
Overhang angle of steel springs, front / rear in degrees	16.00 / 13.90
Height of loading edge with steel springs in mm ( <i>ft</i> )	671 (2.2)
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	380 (13.4) / -
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1200 (42.4)

\*Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tires/wheels used