

Audi Q2



30 TFSI 81 kW

Engine / electrics

Engine type	Inline 3-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	999 / 74.5 x 76.4 / 11.5
Max. power output in kW (PS) / at rpm	81 (110) / 5500
Max. torque in Nm (<i>lb-ft</i>) / at rpm	200 (147.5) / 2000 - 3000
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6d-ISC-FCM
Max. electrical output at 12V in kW	1.3
On-board voltage 1 in volts	12

Drivetrain / transmission

Drive type	Front-wheel drive
Clutch	Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel
Transmission type	6-speed manual gearbox
Transmission ratio in 1 st /2 nd gear	3.769 / 1.947
Transmission ratio in 3 rd /4 th gear	1.281 / 0.973
Transmission ratio in 5 th /6 th gear	0.778 / 0.642
Reverse gear ratio / final drive ratio 1-2 / 2-3	3.182 / 4.688 / -

Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Torsion-beam rear axle
Tires (basic)	205/60 R 16
Wheels (basic)	Alloy 6 J x 16"
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	14.1
Turning circle in m (<i>ft</i>)	11.1 (36.4)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist

Performance / fuel / acoustics

Top speed in km/h (<i>mph</i>)	197 (122.4)
Acceleration, 0-100 km/h (0-62.1 <i>mph</i>)	11.2
Fuel type / octane value / fuel standard	Gasoline / 95 / DIN EN 228
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	69.7 / 66

Consumption / emission*

Efficiency class	B
Fuel consumption, urban / extra-urban / combined according to NEDC in l/100 km (US mpg)	6.3 - 6.2 (37.3 - 37.9) / 4.8 - 4.4 (49.0 - 53.5) / 5.4 - 5.1 (43.6 - 46.1)
CO ₂ emissions, combined according to NEDC in g/km (g/mi)	123 - 116 (197.9 - 186.7)

Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 18 / 18

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (lb)	1250 (2755.8) / 1325 (2921.1) / 1815 (4001.4)
Front / rear axle load limit in kg (lb)	950 (2094.4) / 925 (2039.3)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	1500 (3306.9) / 1300 (2866.0) // 660 (1455.1)
Roof load limit / permissible nose weight in kg (lb)	60 (132.3) / 75 (165.3)

Capacities

Cooling system capacity (incl. heating) in l (US gal)	9 (2.4)
Engine oil capacity, including filter (change volume) in l (US qt)	4 (4.2)
Fuel tank capacity / optional in l (US gal)	50 (13.2) / -

Dimensions / body

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient C _d / frontal area A in m ² (sq ft)	0.31 / 2.29 (24.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / air springs) in mm (ft)	4208 (13.8) / 1794 (5.9) / 1537 (5.0) / -
Vehicle width, including mirrors, in mm (in)	2009 (6.6)
Wheelbase // track width front/rear in mm (ft)	2601 (8.5) // 1546 (5.07) / 1542 (5.06)
Height of loading edge in mm (ft)	740 (2.4)
Open luggage compartment - behind the 2 nd seat row in l (cu ft)	405 (14.3)
Largest luggage capacity - behind the 1 st seat row in l (cu ft)	1050 (37.1)

*Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used