

<b>Technical Data</b>		<b>Audi A3 Sportback 35 TFSI (110 kW)</b>	
<b>Program for Germany</b>		Status: 11/23/2020	
<b>Engine / electrics</b>			
Engine type	Inline 4-cylinder engine		
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder		
Displacement in cc / bore x stroke in mm / compression	1498 / 74.5 x 85.9 / 10.5		
Max. power output in kW (PS) / rpm	110 (150) / 5000 - 6000		
Max. torque in Nm ( <i>lb-ft</i> ) / at rpm	250 ( <i>184.4</i> ) / 1500 - 3500		
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler		
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter		
Emissions standard	Euro 6 d-ISC-FCM		
Start-stop / REM	yes / yes		
Battery in A / Ah	320 / 59		
Max. electrical output at 12V in kilowatts	1.6		
On-board voltage 1 in volts	12		
<b>Drivetrain / transmission</b>			
Drive type	Front-wheel drive		
Clutch	Hydraulically actuated dry clutches, asbestos/lead-free linings, dual-mass flywheel		
Transmission type	6-speed manual gearbox		
Transmission ratio in 1st/2nd gear	3.750 / 2.100		
Transmission ratio in 3rd/4th gear	1.276 / 0.878		
Transmission ratio in 5th/6th gear	0.674 / 0.510		
Reverse gear ratio / final drive ratio 1-2 / 2-3	3.583 / 4.235 / 4.235		
<b>Suspension / steering / brakes</b>			
Type and design of front-axle suspension	MacPherson struts, front		
Type and design of rear-axle suspension	4-link rear axle		
Steering	Electromechanical steering with speed-dependent power assistance		
Steering ratio	14.9		
Turning circle ( <i>ft</i> )	11.1 (36.4)		
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist		
Tires (basic)	205/55 R 16		
Wheels (basic)	Alloy 7 J x 16"		
<b>Performance / acoustics</b>			
Top speed in km/h ( <i>mph</i> )	224 ( <i>139.2</i> )		
Limited	no		
Acceleration, 0-100 km/h ( <i>0-62.1 mph</i> )	8.7		
Fuel type / octane value	Gasoline / 95		
Fuel standard	DIN EN 228 (gasoline)		
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	73.6 / 67		

<b>Consumption / emissions*</b>	
Fuel consumption, urban / extra-urban / combined in l/100 km (US mpg)	6.7 - 6.5 (35.1 - 36.2) / 4.7 - 4.4 (50.0 - 53.5) / 5.4 - 5.2 (43.6 - 45.2)
CO <sub>2</sub> emissions, combined in g/km (g/mi)	125 - 119 (201.2 - 191.5)
<b>Servicing / guarantee (Germany)</b>	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	14 / 20 / 21
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg (lb)	1285 (2832.9) / 1360 (2998.3) / 1835 (4045.5)
Front/rear axle load limit in kg (lb)	965 (2127.5) / 960 (2116.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	1700 (3747.9) / 1500 (3306.9) // 680 (1499.1)
Roof load limit / permissible nose weight in kg (lb)	75 (165.3) / 80 (176.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in l (US gal)	11.2 (3.0)
Engine oil capacity, including filter (change volume) in l (US qt)	4.3 (4.5)
Fuel tank capacity in l (US gal)	50 (13.2)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> (sq ft)	0.29 / 2.17 (23.4)
Standard dimensions (length / width excluding mirrors / height with steel springs) in mm (ft)	4343 (14.2) / 1816 (6.0) / 1449 (4.8)
Width including mirrors in mm (ft)	1984 (6.5)
Wheelbase / track width front/rear in mm (ft)	2636 (8.6) / 1554 (5.1) / 1525 (5.0)
Height of loading edge with steel springs in mm (ft)	671 (2.2)
Open luggage compartment - behind the 2nd seat row in l (cu ft)	380 (13.4)
Largest luggage capacity - behind the 1st seat row in l (cu ft)	1200 (42.4)

\*Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tires/wheels used