

Technical Data		Audi A6 allroad 45 TDI quattro S tronic (180 kW)
Program for Germany	Status: 12/14/2020	
Engine / electrics		
Engine type	V6 engine	
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	2967 / 83.0 x 91.4 / 16.3	
Max. power output in kW (PS) / rpm	180 (245) / 3500 - 4750	
Max. torque in Nm (lb-ft) / at rpm	500 (368.8) / 1500 - 3250	
Mixture preparation	Common rail fuel injection system, intercooler	
Exhaust emission control	NO _x oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter	
Emissions standard	Euro-6d-ISC-FCM	
Start-stop / recuperation management	yes / yes	
Battery in A / Ah	380 / 68	
Max. electrical output at 12V in kilowatts	3	
On-board voltage 1 in volts	12	
On-board voltage 2 in volts	48	
Drivetrain / transmission		
Drive type	quattro all-wheel drive with ultra technology	
Type of center differential	Electronically controlled multi-plate clutch	
Type of rear axle differential	quattro ultra	
Clutch	Dual clutch	
Transmission type	7-speed S tronic	
Transmission ratio in 1st/2nd gear	3.188 / 2.190	
Transmission ratio in 3rd/4th gear	1.517 / 1.057	
Transmission ratio in 5th/6th gear	0.738 / 0.508	
Transmission ratio in 7th/8th gear	0.386 / -	
Reverse gear ratio / final drive ratio 1-2	2.75 / 4.410	
Suspension / steering / brakes		
Type and design of front-axle suspension	5-link front axle; tubular anti-roll bar; air spring suspension	
Type and design of rear-axle suspension	5-link rear axle; tubular anti-roll bar; air spring suspension	
Steering	Electromechanical progressive steering with speed-dependent power assistance	
Steering ratio	15.9	
Turning circle in m (ft)	12.2 (40.0)	
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist	
Tires (basic)	235/55 R 18	
Wheels (basic)	Alloy 8 J x 18"	
Performance / acoustics		
Top speed in km/h (mph)	250 (155.3)	
Limited	yes	
Acceleration, 0-100 km/h (0-62.1 mph)	6.6	
Fuel type / octane value	Diesel / -	
Fuel standard	DIN EN 590 (diesel)	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	75.0 / 68	

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	8.0-7.8 (29.4-30.2) / 5.2-5.1 (45.2-46.1) / 6.2-6.1 (37.9-38.6)
CO ₂ emissions, combined in grams per kilometer (<i>g/mi</i>)	164-160 (263.9-257.5)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 26 / 25
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1945 (4288.0) / 2020 (4453.3) / 2625 (5787.1)
Front/rear axle load limit in kg (<i>lb</i>)	1275 (2810.9) / 1440 (3174.7)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	2500 (5511.6) / 2500 (5511.6) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	100 (220.5) / 100 (220.5)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	15.7 (4.1)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	6.1 (6.4)
Fuel tank capacity / optional fuel tank capacity in liters (<i>US gal</i>)	63 (16.6) / 73 (19.3)
AdBlue fuel tank capacity / AdBlue optional fuel tank capacity in liters (<i>US gal</i>)	12 (3.2) / 22 (5.8)
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.30 / 2.38 (25.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4951 (16.2) / 1902 (6.2) / - / 1497 (4.9)
Width including mirrors in mm (<i>ft</i>)	2110 (6.9)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2925 (9.6) / 1645 (5.4) / 1611 (5.3)
Overhang angle of air springs, front/rear in degrees	14.3 / 17.9
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	- / 636 (2.1)
Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>)	565 (20.0) / -
Largest luggage capacity - behind the 1st seat row in l (<i>cu ft</i>)	1680 (59.3)

*Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used