

Technical Data		Audi Q3 45 TFSI quattro S tronic (180 kW)	
Program for Germany		Date: 02/02/2021	
Engine / electrics			
Engine type	Inline 4-cylinder engine		
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder		
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 9.6		
Max. power output in kW (PS) / rpm	180 kW (245 hp) / 5000 - 6500		
Max. torque in Nm (lb-ft) / at rpm	370 (272.9) / 1600 - 4300		
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler		
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter		
Emissions standard	Euro-6d-ISC-FCM		
Start-stop / recuperation management	yes / yes		
Battery in A / Ah	320 / 59		
Max. electrical output at 12V in kilowatts	1.6		
On-board voltage 1 in volts	12		
Drivetrain / transmission			
Drive type	All-wheel drive		
Clutch	Dual clutch		
Transmission type	7-speed S tronic		
Transmission ratio in 1st/2nd gear	3.400 / 2.7500		
Transmission ratio in 3rd/4th gear	1.767 / 0.925		
Transmission ratio in 5th/6th gear	0.705 / 0.755		
Transmission ratio in 7th/8th gear	0.635 / -		
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.900 / 4.813 / 3.667		
Suspension / steering / brakes			
Type and design of front-axle suspension	MacPherson struts, front		
Type and design of rear-axle suspension	4-link rear axle		
Steering	Electromechanical progressive steering with speed-dependent power assistance		
Steering ratio	14.8		
Turning circle in m (ft)	11.8 (38.7)		
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist		
Tires (basic)	215/65 R 17		
Wheels (basic)	Alloy 7 J x 17"		
Performance / acoustics			
Top speed in km/h (mph)	238 (147.9)		
Limited	no		
Acceleration, 0-100 km/h (0-62.1 mph)	5.8		
Fuel type / octane value	Gasoline / 95		
Fuel standard	DIN EN 228 (gasoline)		
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	75.0 / 67		

Consumption / emissions*	
Fuel consumption: city / highway / combined in l/100 km (US mpg)	9.2 - 8.9 (25.6 - 26.4) / 6.6 - 6.1 (35.6 - 38.6) / 7.5 - 7.1 (31.4 - 33.1)
CO ₂ emissions, combined in g/km (g/mi)	172 - 163 (276.8 - 262.3)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 21 / 23
Weights / loads	
Unladen weight without driver / with driver in kg (lb)	1620 (3571.5) / 1695 (3736.8)
Gross weight limit min. / max. in kg (lb)	2150 (4739.9) / 2200 (4850.2)
Front axle load limit in kg (lb)	1150 (2535.3)
Rear axle load limit min. / max. in kg (lb)	1080 (2381.0) / 1135 (2502.2)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	2100 (4629.7) / 2100 (4629.7) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (lb)	75 (165.3) / 90 (198.4)
Capacities	
Cooling system capacity (incl. heating) in l (US gal)	9.2 (2.4)
Engine oil capacity, including filter (change volume) in l (US qt)	5.7 (6.0)
Fuel tank capacity in l (US gal)	60 (15.9)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (sq ft)	0.33 / 2.44 (26.3)
Standard dimensions (length / width excluding mirrors / height with steel springs) in mm (ft)	4485 (14.7) / 1849 (6.1) / 1616 (5.3)
Width including mirrors in mm (ft)	2024 (6.6)
Wheelbase / track width front/rear in mm (ft)	2680 (8.8) / 1541 (5.1) / 1574 (5.2)
Overhang angle of steel springs, front/rear in degrees	18.80 / 16.20
Height of loading edge with steel springs in mm (ft)	748 (2.5)
Open luggage compartment - behind the 2nd seat row in l (cu ft)	530 (18.7)
Largest luggage capacity - behind the 1st seat row in l (cu ft)	1525 (53.9)

*Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used