

Audi Q2



40 TFSI quattro S tronic 140 kW

Engine / electrics

Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 12.2
Max. power output in kW (PS) / at rpm	140 (190) / 4200 - 6000
Max. torque in Nm (<i>lb-ft</i>) / at rpm	320 (236.0) / 1500 - 4100
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6d-ISC-FCM
Max. electrical output at 12V in kW	1.6
On-board voltage 1 in volts	12

Drivetrain / transmission

Drive type	All-wheel drive
Type of center differential	Electronically controlled multi-plate clutch
Clutch	2 hydraulically controlled multi-plate clutches in an oil bath, dual-mass flywheel
Transmission type	7-speed S tronic
Transmission ratio in 1 st /2 nd gear	3.400 / 2.750
Transmission ratio in 3 rd /4 th gear	1.767 / 0.925
Transmission ratio in 5 th /6 th gear	0.705 / 0.755
Transmission ratio in 7 th /8 th gear	0.635 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.9 / 4.471 / 3.304

Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Tires (basic)	205/60 R 16
Wheels (basic)	Steel 6 J x 16"
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	14.1
Turning circle in m (<i>ft</i>)	11.1 (36.4)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist

Performance / fuel / acoustics

Top speed in km/h (<i>mph</i>)	231 (143.5)
Acceleration, 0-100 km/h (0-62.1 <i>mph</i>)	6.7
Fuel type / octane value / fuel standard	Gasoline / 95 / DIN EN 228
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	74 / 67

Consumption / emission*

Efficiency class	C
Fuel consumption, urban / extra-urban / combined according to NEDC in l/100 km (US mpg)	7.9 - 7.5 (29.8 - 31.4) / 5.9 - 5.6 (39.9 - 42.0) / 6.6 - 6.3 (35.6 - 37.3)
CO ₂ emissions, combined according to NEDC in g/km (g/mi)	151 - 144 (243.0 - 231.7)

Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 20 / 21

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (lb)	1460 (3218.7) / 1535 (3384.1) / 2045 (4508.5)
Front / rear axle load limit in kg (lb)	1090 (2403.0) / 1030 (2270.8)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	1700 (3747.9) / 1500 (3306.9) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (lb)	60 (132.3) / 75 (165.3)

Capacities

Cooling system capacity (incl. heating) in l (US gal)	9.9 (2.6)
Engine oil capacity, including filter (change volume) in l (US qt)	6.6 (7.0)
Fuel tank capacity / optional in l (US gal)	55 (14.5) / -

Dimensions / body

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient C _d / frontal area A in m ² (sq ft)	0.32 / 2.29 (24.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / air springs) in mm (ft)	4208 (13.8) / 1794 (5.9) / 1537 (5.0) / -
Vehicle width, including mirrors, in mm (in)	2009 (6.6)
Wheelbase // track width front/rear in mm (ft)	2593 (8.5) // 1547 (5.075) / 1549 (5.082)
Overhang angle of steel springs, front / rear in degrees	20.20 / 18.00
Height of loading edge in mm (ft)	740 (2.4)
Open luggage compartment - behind the 2 nd seat row in l (cu ft)	405 (14.3)
Largest luggage capacity - behind the 1 st seat row in l (cu ft)	1050 (37.1)

*Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used