

Audi Q4

40 e-tron 150 kW



Drivetrain / transmission / battery

| | |
|--|---------------------|
| Drive type | Rear-wheel drive |
| Number of electric motors front axle / rear axle | 0 / 1 |
| Transmission type | 1-speed / automatic |
| Peak electrical output in kW | 150 |
| Continuous electrical output in kW | 70 |
| Battery type / number of cells | Lithium-Ion / 288 |
| Gross / net battery capacity in kWh | 82 / 76.6 |
| Max. charging capacity AC / DC in kW | 11 / 135 |
| Charging time DC 5-80% in min | 29 / - |
| Charging time AC 0-100%, 3ph 16A@230V in min | 450 |
| On-board voltage 1 in volts | 12 |
| On-board voltage 2 in volts | 400 |

Suspension / steering / brakes

| | |
|--|--|
| Type and design of front-axle suspension | McPherson struts, front |
| Type and design of rear-axle suspension | 4-link rear axle |
| Tires (basic) | 235/55 R 19 255/50 R 19 |
| Wheels (basic) | Steel 8 J x 19 |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Steering ratio | 15.6 |
| Turning circle in m (ft) | 10.2 (33.5) |
| Brake system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper |

Performance / range / acoustics

| | |
|---|---------------------------|
| Top speed in km/h (mph) | 160 (99.4) (limited) |
| electrical acceleration, 0-100 km/h (62.1 mph) in s | 8.5 |
| Electrical range, combined according to WLTP in km (mi) | 528 - 447 (328.1 - 277.8) |

Consumption / emission*

| | |
|--|-------------|
| Electric power consumption, combined according to WLTP in kWh/100 km (62.1 mi) | 19.6 - 16.6 |
| CO ₂ emissions, combined in g/km (g/mi) | 0 |

Servicing / guarantee (Germany)

| | |
|--|------------------|
| Service interval | 2 years |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 years |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 16 / 22 / 22 |

Weights / loads

| | |
|--|--|
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 2050 / 2125 / 2640 (4519.5 / 4684.8 / 5820.2) |
| Front / rear axle load limit in kg (<i>lb</i>) | 1195 / 1505 (2634.5 / 3318.0) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 1200 / 1000 // 750 (2645.5 / 2204.6 // 1653.5) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 / 75 (165.3 / 165.3) |
| Permissible nose weight optional in kg (<i>lb</i>) | |

Dimensions / body

| | |
|--|---|
| Body type / number of doors / number of seats | Unitary steel / 5 / 5 |
| Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>) | 0.28 / 2.56 (27.6) |
| Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>) | 4588 / 1865 / 1632 / - (15.1 / 6.1 / 5.4 / -) |
| Vehicle width, including mirrors, in mm (<i>in</i>) | 2108 (6.9) |
| Wheelbase // track width front / rear in mm (<i>ft</i>) | 2764 // 1587 / 1565 (9.1 // 5.2 / 5.1) |
| Overhang angle of steel springs, front / rear in degrees | 16.90 / 19.40 |
| Height of loading edge in mm (<i>ft</i>) | 783 (2.6) |
| Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>) | 520 (18.4) |
| Largest luggage capacity - behind the 1st seat row in l (<i>cu ft</i>) | 1490 (52.6) |

***Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures.**