

# Audi Q4 Sportback



## 35 e-tron 125 kW

### Drivetrain / transmission / battery

Drive type	Rear-wheel drive
Number of electric motors front axle / rear axle	0 / 1
Transmission type	1-speed / automatic
Peak electrical output in kW	125
Continuous electrical output in kW	70
Electrical torque output in Nm ( <i>lb-ft</i> )	310 (228.6)
Battery type / number of cells	Lithium-Ion / 192
Gross / net battery capacity in kWh	55 / 51.5
Max. charging capacity AC / DC in kW	7.2 / 110
Charging time AC 0-100%, 3ph 16A@230V in min	450
Charging time AC 0-100%, 3ph 16A@230V optional in min	36
On-board voltage 1 in volts	12
On-board voltage 2 in volts	400

### Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Tires (basic)	235/55 R 19   255/50 R 19
Wheels (basic)	Steel 8 J x 19"
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.6
Turning circle in m ( <i>ft</i> )	10.2 (33.5)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper

### Performance / range / acoustics

Top speed in km/h ( <i>mph</i> )	160 (99.4) (limited)
electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in s	9.0
Electrical range, combined according to WLTP in km ( <i>mi</i> )	349 - 317 (216.9 - 197.0)
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 66

### Consumption / emission\*

Efficiency class	A+++
Electric power consumption, combined according to NEDC in kWh/100 km (62.1 <i>mi</i> )	15.7 - 15.0
Electric power consumption, combined according to WLTP in kWh/100 km (62.1 <i>mi</i> )	18.5 - 16.5
CO2 emissions, combined in g/km ( <i>g/mi</i> )	0

---

**Servicing / guarantee (Germany)**

---

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 22 / 22

---

**Weights / loads**

---

Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1895 / 1970 / 2475 (4177.8 / 4343.1 / 5456.4)
Front / rear axle load limit in kg ( <i>lb</i> )	1145 / 1400 (2524.3 / 3086.5)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1200 / 1000 // 750 (2645.5 / 2204.6 // 1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 / 75 (165.3 / 165.3)

---

**Dimensions / body**

---

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient $C_d$ / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.27 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4588 / 1865 / 1614 / - (15.1 / 6.1 / 5.3 / -)
Vehicle width, including mirrors, in mm ( <i>in</i> )	2108 (6.9)
Wheelbase // track width front / rear in mm ( <i>ft</i> )	2764 // 1587 / 1565 (9.1 // 5.2 / 5.1)
Height of loading edge in mm ( <i>ft</i> )	783 (2.6)
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	535 (18.9)
Largest luggage capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1460 (51.6)

\* Figures depend on the equipment selected.