

Audi Q4 Sportback



50 e-tron quattro 220 kW

Drivetrain / transmission / battery

Drive type	All-wheel drive
Number of electric motors front axle / rear axle	1 / 1
Transmission type	1-speed / automatic
Peak electrical output in kW	220
Continuous electrical output in kW	77
Electrical torque output in Nm (<i>lb-ft</i>)	460 (339.3)
Battery type / number of cells	Lithium-Ion / 288
Gross / net battery capacity in kWh	82 / 76.6
Max. charging capacity AC / DC in kW	11.0 / 135
Charging time AC 0-100%, 3ph 16A@230V in min	450
Charging time AC 0-100%, 3ph 16A@230V optional in min	36
On-board voltage 1 in volts	12
On-board voltage 2 in volts	400

Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Tires (basic)	235/55 R 19 255/50 R 19
Wheels (basic)	Steel 8 J x 19"
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.6
Turning circle in m (<i>ft</i>)	11.5 (37.7)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper

Performance / range / acoustics

Top speed in km/h (<i>mph</i>)	180 (111.8) (limited)
electrical acceleration, 0-100 km/h (62.1 <i>mph</i>) in s	6.2
Electrical range, combined according to WLTP in km (<i>mi</i>)	498 - 418 (309.4 - 259.7)
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 66

Consumption / emission*

Efficiency class	A+++
Electric power consumption, combined according to NEDC in kWh/100 km (62.1 <i>mi</i>)	18.1 - 16.1
Electric power consumption, combined according to WLTP in kWh/100 km (62.1 <i>mi</i>)	21.0 - 17.5
CO2 emissions, combined in g/km (<i>g/mi</i>)	0

Servicing / guarantee (Germany)

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 24 / 22

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	2140 / 2215 / 2715 (4717.9 / 4883.2 / 5985.6)
Front / rear axle load limit in kg (<i>lb</i>)	1275 / 1510 (2810.9 / 3329.0)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1400 / 1200 // 750 (3086.5 / 2645.5 // 1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 / 75 (165.3 / 165.3)

Dimensions / body

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>)	0.27 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4588 / 1865 / 1614 / - (15.1 / 6.1 / 5.3 / -)
Vehicle width, including mirrors, in mm (<i>in</i>)	2108 (6.9)
Wheelbase // track width front / rear in mm (<i>ft</i>)	2764 // 1587 / 1565 (9.1 // 5.2 / 5.1)
Height of loading edge in mm (<i>ft</i>)	783 (2.6)
Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	535 (18.9)
Largest luggage capacity - behind the 1st seat row in l (<i>cu ft</i>)	1460 (51.6)

* Figures depend on the equipment selected.