

Audi Q4 Sportback



40 e-tron 150 kW

Drivetrain / transmission / battery

Drive type	Rear-wheel drive
Number of electric motors front axle / rear axle	0 / 1
Transmission type	1-speed / automatic
Peak electrical output in kW	150
Continuous electrical output in kW	70
Electrical torque output in Nm (<i>lb-ft</i>)	310 (228.6)
Battery type / number of cells	Lithium-Ion / 288
Gross / net battery capacity in kWh	82 / 76.6
Max. charging capacity AC / DC in kW	11.0 / 135
Charging time AC 0-100%, 3ph 16A@230V in min	450
Charging time AC 0-100%, 3ph 16A@230V optional in min	29
On-board voltage 1 in volts	12
On-board voltage 2 in volts	400

Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Tires (basic)	235/55 R 19 255/50 R 19
Wheels (basic)	Steel 8 J x 19"
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.6
Turning circle in m (<i>ft</i>)	10.2 (33.5)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper

Performance / range / acoustics

Top speed in km/h (<i>mph</i>)	160 (99.4) (limited)
electrical acceleration, 0-100 km/h (62.1 <i>mph</i>) in s	8.5
Electrical range, combined according to WLTP in km (<i>mi</i>)	528 - 452 (328.1 - 280.9)
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 66

Consumption / emission*

Efficiency class	A+++
Electric power consumption, combined according to NEDC in kWh/100 km (62.1 <i>mi</i>)	17.0 - 15.6
Electric power consumption, combined according to WLTP in kWh/100 km (62.1 <i>mi</i>)	19.5 - 16.7
CO2 emissions, combined in g/km (<i>g/mi</i>)	0

Servicing / guarantee (Germany)

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 22 / 22

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	2045 / 2120 / 2625 (4508.5 / 4673.8 / 5787.1)
Front / rear axle load limit in kg (<i>lb</i>)	1200 / 1495 (2645.5 / 3295.9)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1200 / 1000 // 750 (2645.5 / 2204.6 // 1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 / 75 (165.3 / 165.3)

Dimensions / body

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>)	0.27 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4588 / 1865 / 1614 / - (15.1 / 6.1 / 5.3 / -)
Vehicle width, including mirrors, in mm (<i>in</i>)	2108 (6.9)
Wheelbase // track width front / rear in mm (<i>ft</i>)	2764 // 1587 / 1565 (9.1 // 5.2 / 5.1)
Height of loading edge in mm (<i>ft</i>)	783 (2.6)
Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	535 (18.9)
Largest luggage capacity - behind the 1st seat row in l (<i>cu ft</i>)	1460 (51.6)

* Figures depend on the equipment selected.