

Technical Data		Audi A7 Sportback 50 TDI quattro tiptronic (210 kW)
Program for Germany	Status: 10/16/2020	
Engine / electrics		
Engine type	V6 engine	
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	2967 / 83.0 x 91.4 / 16.3	
Max. power output in kW (PS) / rpm	210 (286) / 3500 - 4000	
Max. torque in Nm (lb-ft) / at rpm	620 (457.3) / 1750 - 3000	
Mixture preparation	Common rail fuel injection system, intercooler	
Exhaust emission control	NO _x oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter	
Emissions standard	EU6	
Start-stop / REM	yes / yes	
Battery in A / Ah	380 / 68	
Max. electrical output at 12V in kilowatts	3	
On-board voltage 1 in volts	12	
On-board voltage 2 in volts	48	
Drivetrain / transmission		
Drive type	quattro permanent all-wheel drive	
Type of center differential	Self-locking	
Type of rear axle differential	Standard	
Clutch	Hydraulic torque converter with lock-up clutch	
Transmission type	8-speed tiptronic	
Transmission ratio in 1st/2nd gear	5.000 / 3.200	
Transmission ratio in 3rd/4th gear	2.143 / 1.720	
Transmission ratio in 5th/6th gear	1.313 / 1.000	
Transmission ratio in 7th/8th gear	0.823 / 0.640	
Reverse gear ratio / final drive ratio 1-2	3.478 / 2.624	
Suspension / steering / brakes		
Type and design of front-axle suspension	5-link front axle; tubular anti-roll bar	
Type and design of rear-axle suspension	5-link rear axle; tubular anti-roll bar	
Steering	Electromechanical progressive steering with speed-dependent power assistance	
Steering ratio	15.9	
Turning circle in m (ft)	12.2 (40.0)	
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist	
Tires (basic)	225/55 R 18	
Wheels (basic)	Alloy 8 J x 18"	
Performance / acoustics		
Top speed in km/h (mph)	250 (155.3)	
Limited	yes	
Acceleration, 0-100 km/h (0-62.1 mph)	5.6	
Fuel type / octane value	Diesel / -	
Fuel standard	DIN EN 590 (Diesel)	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	73.0 / 68	

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	7.6 - 7.3 (30.9 - 32.2) / 5.0 - 4.8 (47.0 - 49.0) / 5.9 - 5.8 (39.9 - 40.6)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	157 - 152 (252.7 - 244.6)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	20 / 28 / 28
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1880 (4144.7) / 1955 (4310.0) / 2535 (5588.7)
Axle load limit, front // rear min. / max. in kg (<i>lb</i>)	1270 (2799.9) // 1305 (2877.0) / 1390 (3064.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	2000 (4409.2) / 2000 (4409.2) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	90 (198.4) / 95 (209.4)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	15.7 (4.1)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	6.1 (6.4)
Fuel tank capacity in liters (<i>US gal</i>)	63 (16.6) / 73 (19.3)
AdBlue fuel tank capacity / optional fuel tank capacity in liters (<i>US gal</i>)	12 (3.2) / 22 (5.8)
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	4+1
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.27 / 2.29 (24.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4969 (16.3) / 1908 (6.3) / 1422 (4.7) / -
Width including mirrors in mm (<i>ft</i>)	2118 (6.9)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2926 (9.6) / 1651 (5.42) / 1637 (5.37)
Overhang angle of steel springs, front / rear in degrees	12.40 / 14.10
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	669 (2.2) / -
Open luggage compartment behind 2nd seat bench in l (<i>cu ft</i>)	535 (18.9)
Largest luggage capacity - behind the 1st seat row in l (<i>cu ft</i>)	1390 (49.1)

*Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used