

Technical Data		Audi Q2 30 TDI (85 kW)
Program for Germany	Status: 12/07/2018	
Engine / electrics		
Engine type	Inline 4-cylinder engine	
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	1598 / 79.5 x 80.5 / 16.2	
Max. power output in kW (hp) / at rpm	85 (116) / 3250 - 4000	
Max. torque in Nm (lb-ft) / at rpm	250 (184.4) / 1750 - 3200	
Mixture preparation	Common rail fuel injection system, intercooler	
Exhaust emission control	Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter	
Emissions standard	EU6	
Start-stop / REM	yes / yes	
Battery in A / Ah	420 / 70	
Max. electrical output at 12V in kilowatts	1.6	
Drivetrain / transmission		
Drive type	Front-wheel drive	
Clutch	Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel	
Transmission type	6-speed manual transmission / manual	
Transmission ratio in 1st/2nd gear	4.111 / 2.118	
Transmission ratio in 3rd/4th gear	1.360 / 0.971	
Transmission ratio in 5th/6th gear	0.733 / 0.592	
Reverse gear ratio / final drive ratio 1-2	4.000 / 3.389	
Suspension / steering / brakes		
Type and design of front-axle suspension	McPherson struts, front	
Type and design of rear-axle suspension	Compound link rear suspension	
Steering	Electromechanical steering with speed-dependent power assistance	
Turning circle / turning circle optional in m (ft)	11.1 (36.4) / -	
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic)	205/60 R 16 92 V not available	
Wheels (basic)	Steel 6.0Jx16"	
Performance / acoustics		
Top speed in km/h (mph)	197 (122.4)	
Acceleration, 0-100 km/h (0-62.1 mph)	10.3	
Fuel type / octane value	Diesel / -	
Fuel standard	EN590	
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	66.8 / 70 / 68	

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	5.6-5.4 (42.0-43.6) / 4.5-4.2 (52.3-56.0) / 4.9-4.6 (48.0-51.1)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	128-121 (206.0-194.7)
Servicing / guarantee (Germany)	
Service interval (<i>mi</i>)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 20 / 23
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1345 (2965.2) / 1420 (3130.6) / 1930 (4254.9)
Front/rear axle load limit in kg (<i>lb</i>)	1045 (2303.8) / 960 (2116.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1700 (3747.9) / 1500 (3306.9) // 710 (1565.3)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	12 (3.2)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	4.7 (5.0)
Fuel tank capacity in liters (<i>US gal</i>)	50 (13.2)
Adblue fuel tank capacity in liters (<i>US gal</i>)	13 (3.4)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / -
Width including mirrors in mm (<i>ft</i>)	2009 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	740 (2.4) / -

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used