

| Technical Data | | Audi Q3 35 TFSI (110 kW) | |
|---|--|---------------------------------|--|
| Program for Germany | | Status: 09/10/2020 | |
| Engine / electrics | | | |
| Engine type | Inline 4-cylinder engine | | |
| Valve gear / number of valves per cylinder | Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder | | |
| Displacement in cc / bore x stroke in mm / compression | 1498 / 74.5 x 85.9 / 10.5 | | |
| Max. power output in kW (PS) / rpm | 110 (150) / 5000 - 6000 | | |
| Max. torque in Nm (<i>lb-ft</i>) / at rpm | 250 (184.4) / 1500 - 3500 | | |
| Mixture preparation | Direct injection, lambda control, knock control, turbocharger, intercooler | | |
| Exhaust emission control | Catalytic converter, oxygen sensor, gasoline particulate filter | | |
| Emissions standard | EU6 | | |
| Start-stop / REM | yes / yes | | |
| Battery in A / Ah | 320 / 59 | | |
| Max. electrical output at 12V in kilowatts | 1.6 | | |
| On-board voltage 1 in volts | 12 | | |
| Drivetrain / transmission | | | |
| Drive type | Front-wheel drive | | |
| Clutch | Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel | | |
| Transmission type | 6-speed manual gearbox | | |
| Transmission ratio in 1st/2nd gear | 3.750 / 1.952 | | |
| Transmission ratio in 3rd/4th gear | 1.200 / 0.878 | | |
| Transmission ratio in 5th/6th gear | 0.711 / 0.604 | | |
| Reverse gear ratio / final drive ratio 1-2 / 2-3 | 3.583 / 4.563 / 4.563 | | |
| Suspension / steering / brakes | | | |
| Type and design of front-axle suspension | McPherson struts, front | | |
| Type and design of rear-axle suspension | 4-link rear axle | | |
| Steering | Electromechanical steering with speed-dependent power assistance | | |
| Steering ratio | 14.8 | | |
| Turning circle in m (<i>ft</i>) | 11.8 (38.7) | | |
| Brake control system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist | | |
| Tires (basic) | 215/65 R 17 | | |
| Wheels (basic) | Alloy 7 J x 17" | | |
| Performance / acoustics | | | |
| Top speed in km/h (<i>mph</i>) | 208 (129.2) | | |
| Limited | no | | |
| Acceleration, 0-100 km/h (0-62.1 <i>mph</i>) | 9.5 | | |
| Fuel type / octane value | Gasoline / 95 | | |
| Fuel standard | DIN EN 228 (gasoline) | | |
| Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A) | 76.1 / 68 | | |

| | |
|--|---|
| Consumption / emissions* | |
| Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>) | 6.8 - 6.7 (34.6 - 35.1) / 5.5 - 4.9 (42.8 - 48.0) / 6.0 - 5.6 (39.2 - 42.0) |
| CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>) | 137 - 128 (220.5 - 206.0) |
| Servicing / guarantee (Germany) | |
| Service interval | 30,000 km (18,641.1 mi) / 2 years, whichever comes first |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 (years) |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 16 / 20 / 20 |
| Weights / loads | |
| Unladen weight without driver / with driver in kg (<i>lb</i>) | 1450 (3196.7) / 1525 (3362.0) |
| Gross weight limit min. / max. in kg (<i>lb</i>) | 2000 (4409.2) / 2045 (4508.5) |
| Front axle load limit in kg (<i>lb</i>) | 1040 (2292.8) |
| Rear axle load limit min. / max. in kg (<i>lb</i>) | 1030 (2270.8) / 1080 (2381.0) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 2000 (4409.2) / 1800 (3968.3) // 750 (1653.5) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 (165.3) / 90 (198.4) |
| Capacities | |
| Cooling system capacity (incl. heating) in liters (<i>US gal</i>) | 11.1 (2.9) |
| Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>) | 4.3 (4.5) |
| Fuel tank capacity in liters (<i>US gal</i>) | 58 (15.3) |
| Dimensions / body | |
| Body type / number of doors | - / 5 |
| Number of seats | 5 |
| Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>) | 0.32 / 2.44 (26.3) |
| Standard dimensions (length / width excluding mirrors / height with steel springs) in mm (<i>ft</i>) | 4484 (14.7) / 1849 (6.1) / 1616 (5.3) |
| Width including mirrors in mm (<i>ft</i>) | 2024 (6.6) |
| Wheelbase / track width front/rear in mm (<i>ft</i>) | 2680 (8.8) / 1584 (5.20) / 1576 (5.17) |
| Overhang angle of steel springs, front/rear in degrees | 18.80 / 16.20 |
| Height of loading edge with steel springs in mm (<i>ft</i>) | 748 (2.5) |
| Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>) | 530 (18.7) / - |
| Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>) | 1525 (53.9) |

*Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used