

<b>Technical Data</b>	<b>Audi Q3 35 TFSI (110 kW)</b>
Program for Germany	Status: 11/08/2018
<b>Engine / electrics</b>	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1498 / 74.5 x 85.9 / 10.5
Max. power output in kW (hp) / at rpm	110 (150) / 5000 - 6000
Max. torque in Nm (lb-ft) / at rpm	250 (184.4) / 1500 - 3500
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Close-coupled catalytic converter, oxygen sensor
Emissions standard	Emission control concept, EU6 AG/H/I
Start-stop / REM	yes / yes
Battery in A / Ah	320 / 59
Max. electrical output at 12V in kilowatts	1.6
On-board voltage 1 in volts	12
<b>Drivetrain / transmission</b>	
Drive type	Front-wheel drive
Clutch	Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel
Transmission type	6-speed manual transmission / manual
Transmission ratio in 1st/2nd gear	3.769 / 2.087
Transmission ratio in 3rd/4th gear	1.324 / 0.977
Transmission ratio in 5th/6th gear	0.975 / 0.814
Reverse gear ratio / final drive ratio 1-2	4.550 / 4.562
<b>Suspension / steering / brakes</b>	
Type and design of front axle suspension	McPherson struts, front
Type and design of rear axle suspension	Four-link rear suspension
Steering	Electromechanical steering with speed-dependent power assistance
Turning circle / turning circle optional in m (ft)	11.8 (38.7) / -
Brake control system	Dual-circuit brake system with ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	215/65 R 17 99 V
Wheels (basic)	Steel 6.5Jx17"
<b>Performance / acoustics</b>	
Top speed in km/h (mph)	211 (131.1)
Governed	no
Acceleration, 0-100 km/h (0-62.1 mph)	9.6
Fuel type / octane value	Gasoline / 95
Fuel standard	DIN EN 228
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	76.1 / 69 / 66

<b>Consumption / emissions*</b>	
Fuel consumption, urban/extra-urban/combined in liters per 100 kilometers ( <i>US mpg</i> )	7.7-7.6 (30.5-30.9) / 5.4-5.1 (43.6-46.1) / 6.3-6.0 (37.3-39.2)
CO <sub>2</sub> emissions combined in grams per kilometer ( <i>g/mi</i> )	145-139 (233.4-223.7)
<b>Servicing / guarantee (Germany)</b>	
Service interval ( <i>mi</i> )	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	17 / 20 / 19
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1460 (3218.7) / 1535 (3384.1) / -
Gross weight limit min. / max. in kg ( <i>lb</i> )	2000 (4409.2) / 2045 (4508.5)
Front/rear axle load limit in kg ( <i>lb</i> )	1050 (2314.9) / -
Rear axle load limit min. / max. in kg ( <i>lb</i> )	1030 (2270.8) / 1080 (2381.0)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	2000 (4409.2) / 1800 (3968.3) // 750 (1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 90 (198.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	11.2 (3.0)
Engine oil capacity, including filter (change volume) in liters ( <i>US qt</i> )	4.3 (4.5)
Fuel tank capacity in liters ( <i>US gal</i> )	60 (15.9)
<b>Dimensions / body</b>	
Body type / number of doors	- / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.32 / 2.44 (26.3)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4484 (14.7) / 1849 (6.07) (with 17/18-inch wheels), 1856 (6.09) (with 19/20-inch wheels) / 1585 (5.2) (without antenna), 1616 (5.3) (with antenna) / not available
Width including mirrors in mm ( <i>ft</i> )	2024 (6.6)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2680 (8.8) / 1584 (5.2) / 1576 (5.17)
Overhang angle of steel springs, front/rear in degrees	18.80 / 16.20
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	748 (2.5) / not available
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	530 (18.7) / not available
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1525 (53.9)
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	530 (18.7)

\* Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tires/wheels used