

<b>Technical Data</b>	<b>Audi Q3 40 TFSI quattro S tronic (140 kW)</b>
Program for Germany	Status: 03/03/2020
<b>Engine / electrics</b>	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 9.6
Max. power output in kW (hp) / at rpm	140 (190) / 4200 - 6700
Max. torque in Nm (lb-ft) / at rpm	320 (236.0) / 1500 - 4200
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, lambda probe, exhaust gas recirculation
Emissions standard	Emission control concept, EU6 BG
Start-stop / REM	yes / yes
Battery in A / Ah	320 / 59
Max. electrical output at 12V in kilowatts	1.8
On-board voltage 1 in volts	12
<b>Drivetrain / transmission</b>	
Drive type	All-wheel drive
Type of rear axle differential	Standard
Clutch	Dual clutch
Transmission type	7-speed S tronic / dual clutch
Transmission ratio in 1st/2nd gear	3.562 / 2.526
Transmission ratio in 3rd/4th gear	1.679 / 1.022
Transmission ratio in 5th/6th gear	0.788 / 0.761
Transmission ratio in 7th/8th gear	0.635 / -
Reverse gear ratio / final drive ratio 1-2	2.789 / 4.733
<b>Suspension / steering / brakes</b>	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Four-link rear suspension
Steering	Electromechanical steering with speed-dependent power assistance
Turning circle / turning circle optional in m (ft)	11.8 (38.7) / -
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	215/65 R 17 99 V
Wheels (basic)	Steel 6.5J x 17"
<b>Performance / acoustics</b>	
Top speed in km/h (mph)	220 (136.7)
Acceleration, 0-100 km/h (0-62.1 mph)	7.4
Fuel type / octane value	Gasoline / 95
Fuel standard	DIN EN 228
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	77.1 / 67 / 66

<b>Consumption / emissions*</b>	
Fuel consumption, urban/extra-urban/combined in liters per 100 kilometers ( <i>US mpg</i> )	9.4-9.2 (25.0-25.6) / 6.4-6.1 (36.8-38.6) / 7.5-7.2 (31.4-32.7)
CO <sub>2</sub> emissions combined in grams per kilometer ( <i>g/mi</i> )	171-165 (275.2-265.5)
<b>Servicing / guarantee (Germany)</b>	
Service interval ( <i>mi</i> )	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	17 / 21 / 22
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1620 (3571.5) / 1695 (3736.8) / -
Gross weight limit min. / max. in kg ( <i>lb</i> )	2150 (4739.9) / 2200 (4850.2)
Front/rear axle load limit in kg ( <i>lb</i> )	1150 (2535.3) / -
Rear axle load limit min. / max. in kg ( <i>lb</i> )	1080 (2381.0) / 1135 (2502.2)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	2100 (4629.7) / 2100 (4629.7) // 750 (1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 90 (198.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	9.2 (2.4)
Engine oil capacity, including filter (change volume) in liters ( <i>US qt</i> )	6.6 (7.0)
Fuel tank capacity in liters ( <i>US gal</i> )	60 (15.9)
<b>Dimensions / body</b>	
Body type / number of doors	- / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.32 / 2.44 (26.3)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4484 (14.7) / 1849 (6.07) (with 17/18-inch wheels), 1856 (6.09) (with 19/20-inch wheels) / 1585 (5.2) (without antenna), 1616 (5.3) (with antenna) / not available
Width including mirrors in mm ( <i>ft</i> )	2024 (6.6)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2680 (8.8) / 1584 (5.20) / 1576 (5.17)
Overhang angle of steel springs, front/rear in degrees	18.80 / 16.20
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	748 (2.5) / not available
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	530 (18.7) / not available
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1525 (53.9)
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	530 (18.7)

\* Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tires/wheels used