

| Technical Data | Audi Q3 45 TFSI quattro S tronic (169 kW) |
|--|---|
| Program for Germany | Status: 11/23/2018 |
| Engine / electrics | |
| Engine type | Inline 4-cylinder engine |
| Valve gear / number of valves per cylinder | Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 1984 / 82.5 x 92.8 / 9.6 |
| Max. power output in kW (hp) / at rpm | 169 (230) / 5000 - 6700 |
| Max. torque in Nm (lb-ft) / at rpm | 350 (258.1) / 1500 - 4400 |
| Mixture preparation | Direct injection, lambda control, knock control, turbocharger, intercooler |
| Exhaust emission control | Catalytic converter, lambda probe, exhaust gas recirculation |
| Emissions standard | Emission control concept, EU6 BG |
| Start-stop / REM | yes / yes |
| Battery in A / Ah | 320 / 59 |
| Max. electrical output at 12V in kilowatts | 1.6 |
| On-board voltage 1 in volts | 12 |
| Drivetrain / transmission | |
| Drive type | All-wheel drive |
| Type of rear axle differential | Standard |
| Clutch | Dual clutch |
| Transmission type | 7-speed S tronic / dual clutch |
| Transmission ratio in 1st/2nd gear | 3.562 / 2.526 |
| Transmission ratio in 3rd/4th gear | 1.679 / 1.022 |
| Transmission ratio in 5th/6th gear | 0.788 / 0.761 |
| Transmission ratio in 7th/8th gear | 0.635 / - |
| Reverse gear ratio / final drive ratio 1-2 | 2.789 / 4.733 |
| Suspension / steering / brakes | |
| Type and design of front-axle suspension | McPherson struts, front |
| Type and design of rear-axle suspension | Four-link rear suspension |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Turning circle / turning circle optional in m (ft) | 11.8 (38.7) / - |
| Brake control system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist |
| Tires (basic) | 215/65 R 17 99 V |
| Wheels (basic) | Steel 6.5J x 17" |
| Performance / acoustics | |
| Top speed in km/h (mph) | 233 (144.8) |
| Governed | yes |
| Acceleration, 0-100 km/h (0-62.1 mph) | 6.3 |
| Fuel type / octane value | Gasoline / 95 |
| Fuel standard | DIN EN 228 |
| Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A) | 77.6 / 67 / 66 |

| | |
|--|--|
| Consumption / emissions* | |
| Fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (<i>US mpg</i>) | 9.7-9.5 (24.2-24.8) / 6.4-6.1 (36.8-38.6) / 7.6-7.3 (30.9-32.2) |
| CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>) | 173-167 (278.4-268.8) |
| Servicing / guarantee (Germany) | |
| Service interval (<i>mi</i>) | 30,000 km (18,641.1) / 2 years, whichever comes first |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 (years) |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 17 / 21 / 22 |
| Weights / loads | |
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 1620 (3571.5) / 1695 (3736.8) / - |
| Gross weight limit min. / max. in kg (<i>lb</i>) | 2150 (4739.9) / 2200 (4850.2) |
| Front/rear axle load limit in kg (<i>lb</i>) | 1150 (2535.3) / - |
| Rear axle load limit min. / max. in kg (<i>lb</i>) | 1080 (2381.0) / 1135 (2502.2) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 2100 (4629.7) / 2100 (4629.7) // 750 (1653.5) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 (165.3) / 90 (198.4) |
| Capacities | |
| Cooling system capacity (incl. heating) in liters (<i>US gal</i>) | 9.8 (2.6) |
| Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>) | 6.6 (7.0) |
| Fuel tank capacity in liters (<i>US gal</i>) | 60 (15.9) |
| Dimensions / body | |
| Body type / number of doors | - / 5 |
| Number of seats | 5 |
| Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>) | 0.33 / 2.44 (26.3) |
| Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>) | 4484 (14.7) / 1849 (6.07) (with 17/18-inch wheels), 1856 (6.09) (with 19/20-inch wheels) / 1585 (5.2) (without antenna), 1616 (5.3) (with antenna) / not available |
| Width including mirrors in mm (<i>ft</i>) | 2024 (6.6) |
| Wheelbase / track width front/rear in mm (<i>ft</i>) | 2680 (8.8) / 1584 (5.20) / 1576 (5.17) |
| Overhang angle of steel springs, front/rear in degrees | 18.80 / 16.20 |
| Height of loading edge with steel springs / air springs in mm (<i>ft</i>) | 748 (2.5) / not available |
| Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>) | 530 (18.7) / not available |
| Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>) | 1525 (53.9) |
| Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>) | 530 (18.7) |

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used