

<b>Technical Data</b>		<b>Audi TT Roadster 45 TFSI quattro S tronic (180 kW)</b>
<b>Program for Germany</b>	Status: 08/28/2020	
<b>Engine / electrics</b>		
Engine type	Inline 4-cylinder engine	
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 9.6	
Max. power output in kW (PS) / rpm	180 (245) / 5000 - 6200	
Max. torque in Nm ( <i>lb-ft</i> ) / at rpm	370 (272.9) / 1600 - 4300	
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler	
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter	
Emissions standard	EU6	
Start-stop / REM	yes / yes	
Battery in A / Ah	380 / 68	
Max. electrical output at 12V in kilowatts	1.6	
On-board voltage 1 in volts	12	
<b>Drivetrain / transmission</b>		
Drive type	All-wheel drive	
Type of rear axle differential	Standard	
Clutch	Dual clutch	
Transmission type	7-speed S tronic	
Transmission ratio in 1st/2nd gear	3.400 / 2.750	
Transmission ratio in 3rd/4th gear	1.767 / 0.925	
Transmission ratio in 5th/6th gear	0.705 / 0.755	
Transmission ratio in 7th/8th gear	0.635 / -	
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.9 / 4.471 / 3.304	
<b>Suspension / steering / brakes</b>		
Type and design of front-axle suspension	McPherson struts, front	
Type and design of rear-axle suspension	4-link rear axle	
Steering	Electromechanical progressive steering with speed-dependent power assistance	
Steering ratio	14.6	
Turning circle in m ( <i>ft</i> )	11 (36.1)	
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic)	225/50 R 17	
Wheels (basic)	Alloy 8 J x 17"	
<b>Performance / acoustics</b>		
Top speed in km/h ( <i>mph</i> )	250 (155.3)	
Limited	yes	
Acceleration, 0-100 km/h (0-62.1 <i>mph</i> )	5.5	
Fuel type / octane value	Gasoline / 95	
Fuel standard	DIN EN 228 (gasoline)	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	84.5 / 70	

<b>Consumption / emissions*</b>	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers ( <i>US mpg</i> )	9.2 - 9.1 (25.6 - 25.8) / 6.2 - 6.1 (37.9 - 38.6) / 7.3 - 7.2 (32.2 - 32.7)
CO <sub>2</sub> emissions combined in grams per kilometer ( <i>g/mi</i> )	166 - 164 (267.2 - 263.9)
<b>Servicing / guarantee (Germany)</b>	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	13 / 19 / 22
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1455 (3207.7) / 1530 (3373.1) / 1810 (3990.4)
Front/rear axle load limit in kg ( <i>lb</i> )	1040 (2292.8) / 825 (1818.8)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	10.1 (2.7)
Engine oil capacity, including filter (change volume) in liters ( <i>US qt</i> )	5.7 (6.0)
Fuel tank capacity in liters ( <i>US gal</i> )	55 (14.5)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 2
Number of seats	2
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.32 / 2.09 (22.5)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4191 (13.7) / 1832 (6.0) / 1355 (4.4) / -
Width including mirrors in mm ( <i>ft</i> )	1966 (6.5)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2505 (8.2) / 1572 (5.2) / 1552 (5.1)
Overhang angle of steel springs, front / rear in degrees	14.70 / 12.20
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	810 (2.7) / -
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	- / 280 (9.9)

\*Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tires/wheels used