

Technical Data	Audi Q2 30 TDI S tronic (85 kW)
Program for Germany	Status: 12/07/2018
Engine / electrics	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1598 / 79.5 x 80.5 / 16.2
Max. power output in kW (hp) / at rpm	85 (116) / 3250 - 4000
Max. torque in Nm (lb-ft) / at rpm	250 (184.4) / 1750 - 3200
Mixture preparation	Common rail fuel injection system, intercooler
Exhaust emission control	Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter
Emissions standard	EU6
Start-stop / REM	yes / yes
Battery in A / Ah	420 / 70
Max. electrical output at 12V in kilowatts	1.6
Drivetrain / transmission	
Drive type	Front-wheel drive
Clutch	Dual clutch
Transmission type	7-speed S tronic / dual clutch
Transmission ratio in 1st/2nd gear	3.500 / 2.087
Transmission ratio in 3rd/4th gear	1.343 / 0.933
Transmission ratio in 5th/6th gear	0.974 / 0.778
Transmission ratio in 7th/8th gear	0.653 / -
Reverse gear ratio / final drive ratio 1-2	3.722 / 4.800
Suspension / steering / brakes	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Compound link rear suspension
Steering	Electromechanical steering with speed-dependent power assistance
Turning circle / turning circle optional in m (ft)	11.1 (36.4) / -
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	205/60 R 16 92 V not available
Wheels (basic)	Steel 6.0Jx16"
Performance / acoustics	
Top speed in km/h (mph)	197 (122.4)
Acceleration, 0-100 km/h (0-62.1 mph)	10.5
Fuel type / octane value	Diesel / -
Fuel standard	EN590
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	66.8 / 69 / 68

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	5.3-4.9 (44.4-48.0) / 4.5-4.2 (52.3-56.0) / 4.8-4.5 (49.0-52.3)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	126-117 (202.8-188.3)
Servicing / guarantee (Germany)	
Service interval (<i>mi</i>)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 20 / 23
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1360 (2998.3) / 1435 (3163.6) / 1945 (4288.0)
Front/rear axle load limit in kg (<i>lb</i>)	1065 (2347.9) / 960 (2116.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1700 (3747.9) / 1500 (3306.9) // 710 (1565.3)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	12 (3.2)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	4.7 (5.0)
Fuel tank capacity in liters (<i>US gal</i>)	50 (13.2)
Adblue fuel tank capacity in liters (<i>US gal</i>)	13 (3.4)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / -
Width including mirrors in mm (<i>ft</i>)	2009 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	740 (2.4) / -

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used