

Technical Data	Audi A4 Sedan 45 TFSI quattro S tronic 195 kW
Program for Germany	Status: 07/22/2021
<b>Engine / electrics</b>	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 9.6
Max. power output in kW (PS) / rpm	195 (265) / 5250 - 6500
Max. torque in Nm (lb-ft) / at rpm	370 (272.9) / 1600 - 4500
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor
Emissions standard	Euro 6d-ISC-FCM
Start-stop / Recuperation management	yes / yes
Battery in A / Ah	380 / 68
Max. electrical output at 12V in kilowatts	3.1
On-board voltage 1 in volts	12
<b>Drivetrain / transmission</b>	
Drive type	quattro all-wheel drive with ultra technology
Type of center differential	Electronically controlled multi-plate clutch
Type of rear axle differential	quattro ultra
Clutch	Dual clutch
Transmission type	7-speed S tronic
Transmission ratio in 1st / 2nd gear	3.188 / 2.190
Transmission ratio in 3rd / 4th gear	1.517 / 1.057
Transmission ratio in 5th / 6th gear	0.738 / 0.508
Transmission ratio in 7th / 8th gear	0.386 / -
Reverse gear ratio / final drive ratio 1-2	2.75 / 4.41
<b>Suspension / steering / brakes</b>	
Type and design of front-axle suspension	5-link front suspension; tubular anti-roll bar
Type and design of rear-axle suspension	5-link rear suspension; tubular anti-roll bar
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.9
Turning circle in m (ft)	11.6 (38.1)
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist
Tires (basic)	225/50 R 17
Wheels (basic)	Alloy 7.5 J x 17"
<b>Performance / acoustics</b>	
Top speed in km/h (mph)	250 (155.34)
Limited	yes
Acceleration, 0-100 km/h (0-62.1 mph)	5.5
Fuel type / octane value	Gasoline / 95
Fuel standard	DIN EN 228 (gasoline)
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in dB (A)	69.2 / - / 67

<b>Consumption / emissions*</b>	
Fuel consumption, urban / extra-urban / combined in l/100 km (US mpg)	9.1 - 8.9 (25.8 - 26.4) / 5.9 - 5.5 (39.9 - 42.8) / 7.1 - 6.8 (33.1 - 34.6)
CO <sub>2</sub> emissions combined in g/km (g/mi)	161 - 155 (259.1 - 249.4)
<b>Servicing / guarantee (Germany)</b>	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 24 / 23
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg (lb)	1570 (3461.3) / 1645 (3626.6) / 2135 (4706.9)
Front/rear axle load limit in kg (lb)	1100 (2425.1) / 1150 (2535.3)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	1900 (4188.8) / 1700 (3747.9) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (lb)	90 (198.4) / 80 (176.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in l (US gal)	7,6 (2.0)
Engine oil capacity, including filter (change volume) in l (US qt)	5.2 (5.5)
Fuel tank capacity in l (US gal)	58 (15.3)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 4
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> (sq ft)	0.27 / 2.20 (23.7)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (ft)	4762 (15.6) / 1847 (6.1) / 1431 (4.7) / -
Width including mirrors in mm (ft)	2022 (6.6)
Wheelbase / track width front/rear in mm (ft)	2820 (9.3) / 1572 (5.2) / 1555 (5.1)
Overhang angle of steel springs, front / rear in degrees	12.50 / 15.30
Height of loading edge with steel springs / air springs in mm (ft)	684 (2.2) / -
Luggage capacity behind 2nd seat bench, open / closed in l (cu ft)	- / 460 (16.2)

\*Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tires/wheels used