

| Technical Data | Audi A4 Sedan 45 TFSI quattro S tronic (180 kW) |
|--|---|
| Program for Germany | Status: 06/10/2019 |
| Engine / electrics | |
| Engine type | Inline 4-cylinder engine |
| Valve gear / number of valves per cylinder | Roller cam follower, continuous intake and exhaust camshaft adjustment / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 1984 / 82.5 x 92.8 / 9.6 |
| Max. power output in kW (PS) / rpm | 180 (245) / 5000 - 6500 |
| Max. torque in Nm (lb-ft) / at rpm | 370 (272.9) / 1600 - 4300 |
| Mixture preparation | Direct injection, lambda control, knock control, turbocharger, intercooler |
| Exhaust emission control | Catalytic converter, oxygen sensor, gasoline particulate filter |
| Emissions standard | EU6 |
| Start-stop / REM | yes / yes |
| Battery in A / Ah | 340 / 58 |
| Max. electrical output at 12V in kilowatts | 3.1 |
| On-board voltage 1 in volts | 12 |
| Drivetrain / transmission | |
| Drive type | quattro all-wheel drive with ultra technology |
| Type of center differential | Electronically controlled multi-plate clutch |
| Type of rear axle differential | quattro ultra |
| Clutch | Dual clutch |
| Transmission type | 7-speed S tronic / dual clutch |
| Transmission ratio in 1st/2nd gear | 3.188 / 2.190 |
| Transmission ratio in 3rd/4th gear | 1.517 / 1.057 |
| Transmission ratio in 5th/6th gear | 0.738 / 0.557 |
| Transmission ratio in 7th/8th gear | 0.433 / - |
| Reverse gear ratio / final drive ratio 1-2 | 2.750 / 4.410 |
| Suspension / steering / brakes | |
| Type and design of front-axle suspension | Five-link front suspension; tubular anti-roll bar |
| Type and design of rear-axle suspension | Five-link rear suspension; tubular anti-roll bar |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Steering ratio min. / max. | 15.9 / 15.9 |
| Steering ratio min. / max. optional | 10.0 / 16.0 |
| Turning circle / turning circle optional in m (ft) | 11.6 (38.1) / not available |
| Brake control system | Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist |
| Tires (basic) | 225/50 R 17 94 Y |
| Wheels (basic) | Forged aluminum 7.5Jx17" |
| Performance / acoustics | |
| Top speed in km/h (mph) | 250 (155.3) |
| Limited | yes |
| Acceleration, 0-100 km/h (0-62.1 mph) | 5.8 |
| Fuel type / octane value | Gasoline / 95 |
| Fuel standard | DIN EN 228 not available |
| Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in dB (A) | 68.4 / - / 68 |

| | |
|--|---|
| Consumption / emissions* | |
| Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>) | 8.7-8.5 (27.0-27.7) / 5.8-5.3 (40.6-44.4) / 6.8-6.5 (34.6-36.2) |
| CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>) | 155-146 (249.4-235.0) |
| Servicing / guarantee (Germany) | |
| Service interval | 30,000 km (18,641.1 mi) / 2 years, whichever comes first |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 (years) |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 14 / 23 / 22 |
| Weights / loads | |
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 1545 (3406.1) / 1620 (3571.5) / 2110 (4651.8) |
| Front/rear axle load limit in kg (<i>lb</i>) | 1080 (2381.0) / 1150 (2535.3) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 1900 (4188.8) / 1700 (3747.9) // 750 (1653.5) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 90 (198.4) / 80 (176.4) |
| Capacities | |
| Cooling system capacity (incl. heating) in liters (<i>US gal</i>) | 8.4 (2.2) |
| Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>) | 5.2 (5.5) |
| Fuel tank capacity in liters (<i>US gal</i>) | 58 (15.3) |
| Dimensions / body | |
| Body type / number of doors | Unitary steel/aluminum composite construction / 4 |
| Number of seats | 5 |
| Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>) | 0.27 / 2.20 (23.7) |
| Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>) | 4762 (15.6) / 1847 (6.1) / 1431 (4.7) / - |
| Width including mirrors in mm (<i>ft</i>) | 2022 (6.6) |
| Wheelbase / track width front/rear in mm (<i>ft</i>) | 2820 (9.3) / 1572 (5.2) / 1555 (5.1) |
| Overhang angle of steel springs, front/rear in degrees | 12.50 / 15.30 |
| Height of loading edge with steel springs / air springs in mm (<i>ft</i>) | 684 (2.2) / - |
| Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>) | Not available / 460 (16.2) |

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used