

<b>Technical Data</b>	<b>Audi Q2 35 TDI (110 kW)</b>
<b>Program for Germany</b>	Status: 09/24/2019
<b>Engine / electrics</b>	
<b>Engine type</b>	Inline 4-cylinder engine
<b>Valve gear / number of valves per cylinder</b>	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
<b>Displacement in cc / bore x stroke in mm / compression</b>	1968 / 81.0 x 95.5 / 16.2
<b>Max. power output in kW (hp) / rpm</b>	110 (150) / 3500 - 4000
<b>Max. torque in Nm (lb-ft) / at rpm</b>	340 (250.8) / 1750 - 3000
<b>Mixture preparation</b>	Common rail fuel injection system, intercooler
<b>Exhaust emission control</b>	Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter
<b>Emissions standard</b>	EU6
<b>Start-stop / REM</b>	yes / yes
<b>Battery in A / Ah</b>	420 / 70
<b>Max. electrical output at 12V in kilowatts</b>	1.6
<b>On-board voltage 1 in volts</b>	12
<b>Drivetrain / transmission</b>	
<b>Drive type</b>	Front-wheel drive
<b>Clutch</b>	Dual clutch
<b>Transmission type</b>	6-speed manual transmission / manual
<b>Transmission ratio in 1st/2nd gear</b>	3.769 / 1.958
<b>Transmission ratio in 3rd/4th gear</b>	1.257 / 0.870
<b>Transmission ratio in 5th/6th gear</b>	0.857 / 0.717
<b>Reverse gear ratio / final drive ratio 1-2</b>	4.549 / 3.450
<b>Suspension / steering / brakes</b>	
<b>Type and design of front-axle suspension</b>	McPherson struts, front
<b>Type and design of rear-axle suspension</b>	Torsion-beam rear axle
<b>Steering</b>	Electromechanical steering with speed-dependent power assistance
<b>Turning circle / turning circle optional in m (ft)</b>	11.1 (36.4) / -
<b>Brake control system</b>	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
<b>Tires (basic)</b>	205/60 R 16 92 V
<b>Wheels (basic)</b>	Steel 6.0Jx16"
<b>Performance / acoustics</b>	
<b>Top speed in km/h (mph)</b>	211 (131.1)
<b>Acceleration, 0-100 km/h (0-62.1 mph)</b>	8.5
<b>Fuel type / octane value</b>	Diesel / -
<b>Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in dB (A)</b>	71.9 / 71 / 67

<b>Consumption / emissions*</b>	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers ( <i>US mpg</i> )	5.6-5.4 (42.0-43.6) / 4.1-3.9 (57.4-60.3) / 4.6-4.5 (51.1-52.3)
CO <sub>2</sub> emissions combined in grams per kilometer ( <i>g/mi</i> )	122-118 (196.3-189.9)
<b>Servicing / guarantee (Germany)</b>	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 20 / 22
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1365 (3009.3) / 1440 (3174.7) / 1955 (4310.0)
Front/rear axle load limit in kg ( <i>lb</i> )	1075 (2370.0) / 960 (2116.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1800 (3968.3) / 1600 (3527.4) // 720 (1587.3)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	60 (132.3) / 75 (165.3)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	12 (3.2)
Engine oil capacity, including filter (change volume) in liters ( <i>US qt</i> )	4.7 (5.0)
Fuel tank capacity in liters ( <i>US gal</i> )	50 (13.2)
AdBlue fuel tank capacity in liters ( <i>US gal</i> )	13 (3.4)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.31 / 2.29 (24.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / n.a.
Width including mirrors in mm ( <i>ft</i> )	2009 (6.6)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	740 (2.4) / n.a.
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	405 (14.3) / n.a.
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1050 (37.1)
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	405 (14.3)

\* Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tires/wheels used