

<b>Technical Data</b>		Audi e-tron 50 quattro
<b>Program for Germany</b>	Status: 02/07/2020	
<b>Engine / electrics</b>		
Peak electrical output in kW	230	
Continuous electrical output in kW	100	
Electrical torque output in Nm ( <i>lb-ft</i> )	540 (398.3)	
Battery type	Lithium-ion	
Battery energy content in kWh	71	
Battery in A / Ah	680 / 60	
Max. electrical output at 12V in kilowatts	3	
On-board voltage 1 in volts	12	
On-board voltage 3 in volts	400	
Start-stop / REM	no / yes	
Emissions standard	-	
<b>Drivetrain / transmission</b>		
Drive type	quattro permanent all-wheel drive	
Transmission type	single-speed	
Transmission ratio in 1st/2nd gear	9.205 / not available	
Reverse gear ratio / final drive ratio 1-2	Not available / 9.205	
<b>Suspension / steering / brakes</b>		
Type and design of front-axle suspension	Five-link front axle; tubular anti-roll bar; air spring suspension	
Type and design of rear-axle suspension	Five-link rear axle; tubular anti-roll bar; air spring suspension	
Steering	Electromechanical progressive steering with speed-dependent power assistance	
Steering ratio	15. Sep	
Turning circle ( <i>ft</i> )	12.2 (40.0)	
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Basic tires, front axle	255/55 R 19 111 H XL (extra load) -	
Basic tires, rear axle	255/55 R 19 111 H XL (extra load) -	
Wheels, front axle	Cast aluminum flow forming 8.5Jx19"	
Wheels, rear axle	Cast aluminum flow forming 8.5Jx19"	
<b>Performance / acoustics</b>		
Top speed in km/h ( <i>mph</i> )	190 (118.1)	
Limited	yes	
Electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in seconds	6.8	
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	- / - / 68	
<b>Consumption / range</b>		
Electric power consumption, combined, in kWh/100 km (62.1 <i>mi</i> )*	26.6-22.4 (WLTP); 24.3-21.9 (NEDC)	
CO <sub>2</sub> emissions, combined, in g/km ( <i>g/mi</i> )	0	
Electrical range based on current consumption in combined WLTP driving cycle in km ( <i>mi</i> )*	up to 336 (208.8)	

<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2370 (5225.0) / 2445 (5390.3) / 3040 (6702.1)
Front/rear axle load limit in kg ( <i>lb</i> )	1510 (3329.0) / 1690 (3725.8)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1800 (3968.3) / 1800 (3968.3) // 750 (1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 80 (176.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	19.6 (5.2)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.28 / 2.65 (28.5)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4901 (16.1) / 1935 (6.3) / not available / 1632 (5.4)
Width including mirrors in mm ( <i>ft</i> )	2192 (7.2)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2928 (9.6) / 1655 (5.43) / 1652 (5.42)
Overhang angle of air spring front/rear in degrees	15.3 / 21.5
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	Not available / 803 (2.6)
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	660 (23.3) / not available
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1725 (60.9)
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	660 (23.3)

\* Figures depend on the equipment selected