

**Technical Data**

Audi e-tron Sportback 50 quattro

Program for Germany

Status: 02/07/2020

**Engine / electrics**

Peak electrical output in kW

230

Continuous electrical output in kW

100

Electrical torque output in Nm (*lb-ft*)

540 (398.3)

Battery type

Lithium-ion

Battery energy content in kWh

71

Battery in A / Ah

380 / 68

Max. electrical output at 12V in kilowatts

3

On-board voltage 1 in volts

12

On-board voltage 3 in volts

400

Start-stop / REM

no / yes

Emissions standard

-

**Drivetrain / transmission**

Drive type

quattro permanent all-wheel drive

Transmission type

single-speed

Transmission ratio in 1st/2nd gear

9.205 / not available

Reverse gear ratio / final drive ratio 1-2

Not available / 9.205

**Suspension / steering / brakes**

Type and design of front-axle suspension

Five-link front axle; tubular anti-roll bar; air spring suspension

Type and design of rear-axle suspension

Five-link rear axle; tubular anti-roll bar; air spring suspension

Steering

Electromechanical progressive steering with speed-dependent power assistance

Steering ratio

15.9

Turning circle (*ft*)

12.2 (40.0)

Brake control system

Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist

Basic tires, front axle

255/55 R 19 111 H XL (extra load) -

Basic tires, rear axle

255/55 R 19 111 H XL (extra load) -

Wheels, front axle

Cast aluminum flow forming 8.5Jx19"

Wheels, rear axle

Cast aluminum flow forming 8.5Jx19"

**Performance / acoustics**Top speed in km/h (*mph*)

190 (118.1)

Limited

yes

Electrical acceleration, 0-100 km/h (62.1 *mph*) in seconds

6.8

Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)

- / - / 68

**Consumption / range**Electric power consumption, combined, in kWh/100 km (62.1 *mi*)\*

26.3-21.6 (WLTP); 23.9-21.4 (NEDC)

CO<sub>2</sub> emissions, combined, in g/km (*g/mi*)

0

Electrical range based on current consumption in combined WLTP driving cycle in km (*mi*)\*

up to 347 (215.6)

<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2370 (5225.0) / 2445 (5390.3) / 3040 (6702.1)
Front/rear axle load limit in kg ( <i>lb</i> )	1510 (3329.0) / 1690 (3725.8)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1800 (3968.3) / 1800 (3968.3) // 750 (1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 80 (176.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	19.6 (5.2)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.25 / 2.65 (28.5)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4901 (16.1) / 1935 (6.3) / not available / 1618 (5.3)
Width including mirrors in mm ( <i>ft</i> )	2189 (7.2)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2928 (9.6) / 1655 (5.4) / 1655 (5.4)
Overhang angle of air spring front/rear in degrees	15.3 / 21.5
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	Not available / 803 (2.6)
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	615 (21.7) / not available
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1665 (58.8)
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	615 (21.7)

\* Figures depend on the equipment selected