

**Technical Data**

Audi e-tron Sportback 55 quattro

Program for Germany

Status: 02/07/2020

**Engine / electrics**

Peak electrical output in kW	300
Continuous electrical output in kW	100
Peak electrical output boost in kW	300
Electrical torque output in Nm ( <i>lb-ft</i> )	561 (413.8)
Electrical torque output boost in Nm ( <i>lb-ft</i> )	664 (489.7)
Battery type	Lithium-ion
Battery energy content in kWh	95
Battery in A / Ah	380 / 68
Max. electrical output at 12V in kilowatts	3
On-board voltage 1 in volts	12
On-board voltage 3 in volts	400
Start-stop / REM	no / yes
Emissions standard	-

**Drivetrain / transmission**

Drive type	quattro permanent all-wheel drive
Transmission type	single-speed
Transmission ratio in 1st/2nd gear	9.205 / not available
Reverse gear ratio / final drive ratio 1-2	Not available / 9.205

**Suspension / steering / brakes**

Type and design of front-axle suspension	Five-link front axle; tubular anti-roll bar; air spring suspension
Type and design of rear-axle suspension	Five-link rear axle; tubular anti-roll bar; air spring suspension
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.9
Turning circle ( <i>ft</i> )	12.2 (40.0)
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Basic tires, front axle	255/55 R 19 111 H XL (extra load) -
Basic tires, rear axle	255/55 R 19 111 H XL (extra load) -
Wheels, front axle	Cast aluminum flow forming 8.5Jx19"
Wheels, rear axle	Cast aluminum flow forming 8.5Jx19"

**Performance / acoustics**

Top speed in km/h ( <i>mph</i> )	200 (124.3)
Limited	yes
Electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in seconds	5.7
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	- / - / 68

**Consumption / range**

Electric power consumption, combined, in kWh/100 km (62.1 <i>mi</i> )*	26.0-21.9 (WLTP); 22.7-20.6 (NEDC)
CO <sub>2</sub> emissions, combined, in g/km ( <i>g/mi</i> )	0
Electrical range based on current consumption in combined WLTP driving cycle in km ( <i>mi</i> )*	up to 446 (277.1)

<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2480 (5467.5) / 2555 (5632.8) / 3150 (6944.6)
Front/rear axle load limit in kg ( <i>lb</i> )	1530 (3373.1) / 1760 (3880.1)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1800 (3968.3) / 1800 (3968.3) // 750 (1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 80 (176.4)
<b>Capacities</b>	
Cooling system capacity (incl. heating) in liters ( <i>US gal</i> )	19.6 (5.2)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.25 / 2.65 (28.5)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4901 (16.1) / 1935 (6.3) / not available / 1616 (5.3)
Width including mirrors in mm ( <i>ft</i> )	2189 (7.2)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2928 (9.6) / 1655 (5.4) / 1655 (5.4)
Overhang angle of air spring front/rear in degrees	15.3 / 21.5
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	Not available / 801 (2.6)
Luggage capacity behind 2nd seat bench, open / closed in l ( <i>cu ft</i> )	615 (21.7) / not available
Largest luggage compartment capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1665 (58.8)
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	615 (21.7)

\* Figures depend on the equipment selected